

# Product data sheet

Version 07/2025

## eBox wr30-L

### Wallbox with IEC 62196-2 Type 2 cable

#### Type SMART / Power 11kW

Mode 3 acc. IEC 61851-1 (VDE 0122-1)

|                        |  |
|------------------------|--|
| <b>Item No.</b>        | <b>00010068</b>                          |
| Input voltage          | 400V AC, 3 phase + N, -20% +15%          |
| Input current          | max. 16A                                 |
| Output voltage         | 230/400V, 3 phase                        |
| Output current         | max. 16A                                 |
| Output power           | max. 11kW                                |
| Charging cable type 2  | 4m                                       |
| DC fault current detc. | electronic, I $\Delta$ n d.c. $\geq$ 6mA |
| RCD*                   | Type A 40A, 30mA                         |
| MCB*                   | 20A, 3-poles, B-character                |
| Energy meter           | MID-compliant (calibrated)               |
| Climate system         | Axial fan + heating                      |
| Storage temperature    | -25 °C to +60 °C                         |
| Operating temperature  | -25 °C to +45 °C                         |
| Protection class       | IP54                                     |
| Material               | Stainless steel 1.4301                   |
| Width                  | 527 mm                                   |
| Depth                  | 240 mm                                   |
| Diameter $\varnothing$ | 114 mm                                   |
| Weight                 | 9.0 kg                                   |
| Interface              | WLAN / LAN / Digital Input               |
| Communication          | eCCP / OCPP 1.6J / Modbus TCP            |
| Authorization          | Plug & Start / eCC APP / RFID            |
| Management             | eCC APP / eLMS                           |
| Master/Slave           | WLAN Mesh                                |
| Packaging              | Carton / 1 Piece                         |
| Dimensions L/W/H       | 660 / 330 / 330 mm                       |
| Shipment weight        | 12.0 kg                                  |



**Available colours** Order No.: 00010068-xx(Colour code)

| Code | Colour  |                         | Unit   |
|------|---|-------------------------|--------|
| 01   |  | Brushed stainless steel | 1 Stk. |
| 27   |  | RAL 9005 black matt     | 1 Stk. |
| 31   |  | RAL desired colour      | 1 Stk. |
| 32   |  | Custom Design           | 1 Stk. |

hesotec electrify gmbh

Rubbertsath 34  
D 46539 Dinslaken

Erros and changes exepted

\*) not included

Tel.: +49(0)2064 60105 60  
E-Mail: [electrify@hesotec.de](mailto:electrify@hesotec.de)

eCC -> electrify Charge Control (APP)  
eCCP -> electrify Charge Control Protocol  
eLMS -> electrify Chargemanagementsystem (Backend)

[electrify.hesotec.de](http://electrify.hesotec.de)

©2021 hesotec electrify gmbh