

# Product data sheet

Version 11/2021

## eSat r10

### Charging Station with IEC 62196-2 Type 2 Socket

Type PREMIUM / Power 22kW



Mode 3 acc. IEC 61851-1 (VDE 0122-1)

<b>Artikelnummer</b>	<b>00010213</b>
Input voltage	400V AC, 3 phase + N, -20% +15%
Input current	max. 32A
Output voltage	230/400V, 3 phase
Output current	max. 32A
Output power	max. 22kW
Charging socket type 2	Lock and release function
DC fault current detc.	electronic, IΔn d.c. >=6mA
RCD*	Type A 40A, 30mA
MCB*	32A, 3-poles, B-character
Energy meter	MID-compliant (calibrated)
Colour display	2,4 Inch, 320x140 px
Climate system	Axial fan + heating
Storage temperature	-25 °C to +60 °C
Operating temperature	-25 °C to +45 °C
Protection class	IP54
Material	Stainless steel 1.4301
Height (total)	970 mm
Height (socket)	750 mm
Diameter Ø	114 mm
Weight	9.2 kg
Interface	WLAN / LAN / Digital Input
Communication	eCCP / OCPP 1.6J / Modbus TCP
Authorization	Plug & Start / eCC APP / RFID
Management	eCC APP / eLMS
Master/Slave	WLAN Mesh
Packaging	Carton / 1 Piece
Dimensions L/W/H	1040 / 200 / 330 mm
Shipment weight	13.5 kg



### Available colours

Order No.: 00010213-xx(Colour code)

Code	Colour		Unit
01		Brushed Stainless steel	1 Piece
27		RAL 9005 black matt	1 Piece

hesotec electrify gmbh

Rubbertsath 34  
D 46539 Dinslaken

Erros and changes exepcted

\*) not included

Tel.: +49(0)2064 60105 60  
E-Mail: [electrify@hesotec.de](mailto:electrify@hesotec.de)

eCC -> electrify Charge Control (APP)  
eCCP -> electrify Charge Control Protocol  
eLMS -> electrify Chargemanagementsystem (Backend)

[electrify.hesotec.de](http://electrify.hesotec.de)

©2021 hesotec electrify gmbh