

Product data sheet

Version 04/2022

eBox wr30-L

Wallbox with IEC 62196-2 Type 2 cable





Type BASE / Power 11kW

Mode 3 acc. IEC 61851-1 (VDE 0122-1)

| | |
|------------------------|--|
| Item No. | 00010240 |
| Input voltage | 400V AC, 3 phase + N, -20% +15% |
| Input current | max. 16A |
| Output voltage | 230/400V, 3 phase |
| Output current | max. 16A |
| Output power | max. 11kW |
| Charging cable type 2 | 8m |
| DC fault current detc. | electronic, I Δ n d.c. \geq 6mA |
| RCD* | Type A 40A, 30mA |
| MCB* | 20A, 3-poles, B-character |
| Climate system | Axial fan + heating |
| Storage temperature | -25 °C to +60 °C |
| Operating temperature | -25 °C to +45 °C |
| Protection class | IP54 |
| Material | Stainless steel 1.4301 |
| Width | 527 mm |
| Depth | 240 mm |
| Diameter \varnothing | 114 mm |
| Weight | 9.5 kg |
| Interface | WLAN / Digital Input |
| Communication | eCCP / Modbus TCP |
| Authorization | Plug & Start / eCC APP / RFID |
| Master/Slave | WLAN Mesh |
| Packaging | Carton / 1 Piece |
| Dimensions L/W/H | 660 / 330 / 330 mm |
| Shipment weight | 13.2 kg |



Available colours Order No.: 00010240-xx(Colour code)

| Code | Colour | | Unit |
|------|---|-------------------------|--------|
| 01 |  | Brushed stainless steel | 1 Stk. |
| 27 |  | RAL 9005 black matt | 1 Stk. |
| 31 |  | RAL desired colour | 1 Stk. |
| 32 |  | Individual Print Design | 1 Stk. |

hesotec electrify gmbh

Rubbertsath 34
D 46539 Dinslaken

Errors and changes exepcted

*) not included

Tel.: +49(0)2064 60105 60
E-Mail: electrify@hesotec.de

eCC -> electrify Charge Control (APP)
eCCP -> electrify Charge Control Protocol
eLMS -> electrify Chagemanagementsystem (Backend)

electrify.hesotec.de

©2021 hesotec electrify gmbh